



	GENERAL STRUCTUR	AL NOTES		
1. THE GENERAL	STRUCTURAL NOTES ARE INTENDED	TO AUGMENT THE I	DRAWINGS AND	
SPECIFICATIO	NS. SHOULD CONFLICTS EXIST BETWE	EEN THE DRAWINGS	AND SPECIFICATIONS	1. SPECIFIC
2. GOVERNING (CODE: OHIO BUILDING CODE - 2007	EDITION.	HALL GOVERN.	GOVERN
3. SEE STRUCTU	RAL PLANS FOR DESIGN SOIL BEARIN	IG PRESSURE AND	LIVE LOADS. LIVE	A. AISC S
LOADS REDU 4. ROOF SNOW	CED IN ACCORDANCE WITH THE GOVE LOAD:	RNING CODE.		B. AISC (
GROUND SNC	DW LOAD (Pg)	- 20 PSF	=	C. AWS S
SNOW EXPOS IMPORTANCE	URE FACTOR (Ce) FACTOR (Is)	- 1.0 - 1.2		D. STRUC WELD
THERMAL FAC	CTOR (CL)	- 1.0		STAN
FLAT ROOF S	DNOW LOAD (PF)	- 24 PSF	=	E. SPECI
BASIC WIND S	PEED	- 90 MPt	+	2. TESTING:
IMPORTANCE	FACTOR (IW)	- 1.15 - FXPOS		A. WELD INDEP
INTERNAL PR	ESSURE COEFFICIENT - (G Cpi)	- ±0.55		NONC
6. SEISMIC LOAI	D: CATEGORY		- 12	REPL/ PENET
IMPORTANCE	FACTOR (Ie)		- 1.5	WELD
MAPPED SPE	CTRAL RESPONSE ACCELERATION AT	SHORT PERIOD (S	(5) - 0.15	B. STRUC REQUI
SITE CLASS			- C	C. A325
SPECTRAL RE	ESPONSE COEFFICIENT AT SHORT PER	RIOD (SDS)	- 0.12	SPECI 3 MATERIA
SEISMIC DESK	SN CATEGORY	PERIOD (SDI)	- C	A. "W" SH
DESIGN BASE	SHEAR		- 11 K	B. CHANI C. ANGLI
BASIC SEISMIC	C FORCE RESISTING SYSTEM:		- 0.050	D. WELD
H-STRUCTL	JRAL STEEL SYSTEMS NOT SPECIFICAL	LLY DETAILED FOR	R SEISMIC RESISTANCE	E. BOLTS
(R=5, Ca=3 DESIGN BY EC) QUIVALENT LATERAL FORCE PROCED	URE.		G. PAINT
7. MECHANICAL	FRAMING LOADS, OPENINGS, AND STI	RUCTURE IN ANY W	AY RELATED TO	1. PR
MECHANICAL SHALL OBTAI	REQUIREMENTS ARE SHOWN FOR BIDI N APPROVAL OF MECHANICAL AND O	DING PURPOSES OI THER TRADES BEF	NLY. CONTRACTOR FORE PROCEEDING WITH	2. ME 3. ME
SUCH PORTIC	N OF THE WORK. EXCESS COST RELA	ATED TO VARIATIO	N IN MECHANICAL	FA
REQUIREMENT	IS TO BE BORNE BY MECHANICAL CO	NTRACTOR. COOF DRAWINGS	RDINATE SIZE AND	4. CONNEC A. DESIG
8. THE STRUCTU	RE IS DESIGNED TO BE SELF-SUPPOR	TING AND STABLE	AFTER THE BUILDING IS	MEME
FULLY COMPLE ERECTION PR	LETED. IT IS SOLELY THE CONTRACTO	OR'S RESPONSIBILI" ENGURE THE SAFET	TY TO DETERMINE TY OF THE BUILDING	B. DESIG MEMB
AND ITS COM	PONENT PARTS DURING ERECTION. T	HIS INCLUDES THE	ADDITION OF WHATEVER	C. CONN
TEMPORARY	BRACING, GUYS, OR TIE-DOWNS WHIC N THE CONTRACTOR'S PROPERTY AF	H MIGHT BE NECES	SARY. SUCH MATERIAL	STEEL AND 1
9. IT IS SOLELY	THE CONTRACTOR'S RESPONSIBILITY	TO FOLLOW ALL A	APPLICABLE SAFETY	DETAI
CODES AND F	REGULATIONS DURING ALL PHASES OF	F CONSTRUCTION.		D. OBTA FABR
RELATING TO	EXISTING CONSTRUCTION AND EXISTING	NG SERVICE ON TH	HE SITE.	E. ALL B
11. THE CONTRAC	CTOR SHALL VERIFY ALL DIMENSIONS	AND LOCATIONS	OF COLUMNS WALLS	UNLES
OPENINGS ET			CEEDING WITH THE WORK	5 MISCELL
OPENINGS ET	C. WITH THE ARCHITECTURAL DRAWING	55 PRIOR TO PROC	CEEDING WITH THE WORK.	5. MISCELLA A. PROV
OPENINGS ET	C. WITH THE ARCHITECTURAL DRAWING	CONCRETE	CEEDING WITH THE WORK.	5. MISCELL, A. PROV SHOW B. STEFI
0PENINGS ET 1. SPECIFICATIO	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED (</u> INS AND STANDARDS:	CONCRETE	CEEDING WITH THE WORK.	5. MISCELL, A. PROV SHOW B. STEEL PURPO
0 PENINGS ET 1. SPECIFICATIO UNLESS SPEC PLACING OF 1	C. WITH THE ARCHITECTURAL DRAWING REINFORCED (INS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COL BARS AND CONCRETE SHALL BE GOV	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE	CEEDING WITH THE WORK.	5. MISCELL, A. PROV SHOW B. STEEL PURPO AND C
OPENINGS ET 1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> NS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL CO BARS AND CONCRETE SHALL BE GOV 9, ACI 301-05, ACI 315-99, AND ACI 318	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE /ERNED BY: 3-05.	CEEDING WITH THE WORK.	5. MISCELL, A. PROV SHOW B. STEEL PURPO AND C COOR THE M
0 PENINGS ET 1. SPECIFICATIO UNLESS SPEC PLACING OF I A. ACI 117-06 B. CRSI RECC C. ACI 306-90	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> NS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL CON BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 OMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND A	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE /ERNED BY: 3-05. REINFORCING BARS	CEEDING WITH THE WORK. TAILING, FABRICATION AND S.	5. MISCELL, A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU
OPENINGS ET 1. SPECIFICATIO UNLESS SPEC PLACING OF I A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRAC	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> WNS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL CON BARS AND CONCRETE SHALL BE GOV 9, ACI 301-05, ACI 315-99, AND ACI 318 OMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A CON	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE /ERNED BY: 3-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA	CEEDING WITH THE WORK. TAILING, FABRICATION AND S. NCRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED	5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-0 REQUI
0 PENINGS ET 1. SPECIFICATIO UNLESS SPEC PLACING OF I A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRAC ABOVE ON THE CONT	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> IFICALLY SHOWN OTHERWISE, ALL CON BARS AND CONCRETE SHALL BE GOV ACI 301-05, ACI 315-99, AND ACI 318 OMMENDED PRACTICE FOR PLACING F O AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A CON N THE SITE AND THE SUPERVISORY PEN- ENTS THEREOF	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE /ERNED BY: 3-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B	CEEDING WITH THE WORK. TAILING, FABRICATION AND S. NCRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED BE THOROUGHLY FAMILIAR WITH	5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D STEEL
1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONTI 2. CONTINGENCI	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> WINS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL CON BARS AND CONCRETE SHALL BE GOV 9, ACI 301-05, ACI 315-99, AND ACI 318 OMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A CON N THE SITE AND THE SUPERVISORY PEN ENTS THEREOF. ES:	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 3-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B	CEEDING WITH THE WORK. TAILING, FABRICATION AND S. NCRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED WE THOROUGHLY FAMILIAR WITH	5. MISCELL, A. PROV SHOW B. STEEL PURPC AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV
1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONTI 2. CONTINGENCI A. PROVIDE I	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> WINS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL CON BARS AND CONCRETE SHALL BE GOV 9, ACI 301-05, ACI 315-99, AND ACI 318 OMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A CON N THE SITE AND THE SUPERVISORY PER ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOLL SPOTS	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 3-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B	CEEDING WITH THE WORK. TAILING, FABRICATION AND S. NCRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED WE THOROUGHLY FAMILIAR WITH DUE TO ACCIDENTAL OVER	5. MISCELL, A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV
1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRAC ABOVE ON THE CONTI 2. CONTINGENCI A. PROVIDE I EXCAVATIO 3. CONCRETE R	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> MAS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL CON BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 OMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A CON N THE SITE AND THE SUPERVISORY PEN ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB:	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 3-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B	CEEDING WITH THE WORK. ETAILING, FABRICATION AND S. NCRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED WE THOROUGHLY FAMILIAR WITH DUE TO ACCIDENTAL OVER	5. MISCELL, A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV RIB FI 6. DRILLED
1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06 B. CRSI RECC C. ACI 306-96 CONTRACT ABOVE ON THE CONTI 2. CONTINGENCI A. PROVIDE I EXCAVATIO 3. CONCRETE R	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> MAS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL CON BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A CON N THE SITE AND THE SUPERVISORY PEN ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB:	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 3-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL	CEEDING WITH THE WORK. ETAILING, FABRICATION AND S. NCRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED WE THOROUGHLY FAMILIAR WITH DUE TO ACCIDENTAL OVER SPECIAL PEOUREMENTS	5. MISCELL, A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV RIB FI 6. DRILLED A. PROV
1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06 B. CRSI RECC C. ACI 306-96 CONTRACT ABOVE ON THE CONTI 2. CONTINGENCI A. PROVIDE I EXCAVATION 3. CONCRETE RECONSTRUCT CLASS 1	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> (MS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL CON BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A CON N THE SITE AND THE SUPERVISORY PEN ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 3-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI	CEEDING WITH THE WORK. ETAILING, FABRICATION AND S. NCRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED WE THOROUGHLY FAMILIAR WITH DUE TO ACCIDENTAL OVER SPECIAL <u>REQUIREMENTS</u>	5. MISCELL, A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV RIB FI 6. DRILLED A. PROV ANCHO
1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06 B. CRSI RECC C. ACI 306-96 CONTRACT ABOVE ON THE CONTI 2. CONTINGENCI A. PROVIDE I EXCAVATIO 3. CONCRETE RECONSTRUCT CLASS 1	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> MS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL CON BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A CON N THE SITE AND THE SUPERVISORY PEN ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE NOT	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE /ERNED BY: 3-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI	CEEDING WITH THE WORK. ETAILING, FABRICATION AND S. NCRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED WE THOROUGHLY FAMILIAR WITH DUE TO ACCIDENTAL OVER SPECIAL REQUIREMENTS	5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV RIB FI 6. DRILLED A. PROV ANCHO EVALL
1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONTI 2. CONTINGENCI A. PROVIDE I EXCAVATIO 3. CONCRETE R 1	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> MS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL CON BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A CON N THE SITE AND THE SUPERVISORY PER ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR CONCRETE	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE /ERNED BY: 3-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI	CEEDING WITH THE WORK. ETAILING, FABRICATION AND S. NCRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED SE THOROUGHLY FAMILIAR WITH DUE TO ACCIDENTAL OVER SPECIAL REQUIREMENTS 5% ±1% AIR CONTENT	5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV RIB FI 6. DRILLED A. PROV ANCHO EVALL APPEN ANCHO
1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONTI 2. CONTINGENCI A. PROVIDE I EXCAVATION 3. CONCRETE RI CLASS 1 2 3	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> (MS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL CON BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A CON N THE SITE AND THE SUPERVISORY PENE ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR SLABS, GRADE	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 3-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 4000 PSI 3500 PSI	CEEDING WITH THE WORK. ETAILING, FABRICATION AND S. NCRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED BE THOROUGHLY FAMILIAR WITH DUE TO ACCIDENTAL OVER SPECIAL REQUIREMENTS 5% ±1% AIR CONTENT	5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV RIB FI 6. DRILLED A. PROV ANCHO ANCHO ANCHO 24" DIA
1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONTI 2. CONTINGENCI A. PROVIDE I EXCAVATION 3. CONCRETE RUNCL CLASS 1 2 3 5	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> (MS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL CON BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A CON N THE SITE AND THE SUPERVISORY PENE ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR CONCRETE INTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 3-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 4000 PSI 3500 PSI 1500 PSI	CEEDING WITH THE WORK. ETAILING, FABRICATION AND S. NCRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED VE THOROUGHLY FAMILIAR WITH DUE TO ACCIDENTAL OVER SPECIAL REQUIREMENTS 5% ±1% AIR CONTENT NO TESTS	5. MISCELL/ A. PROV SHOW B. STEEL PURPC AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV F. PROV RIB FI 6. DRILLED A. PROV ANCHO ANCHO & ANCHO & ANCHO & TIA Y" DIA Y" DIA
1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONTI 2. CONTINGENCI A. PROVIDE I EXCAVATION 3. CONCRETE RUNCL CLASS 1 2 3 5 SUBMIT CC	C. WITH THE ARCHITECTURAL DRAWING REINFORCED (NS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COL BARS AND CONCRETE SHALL BE GOV ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F O AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A COL N THE SITE AND THE SUPERVISORY PER ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: LOCATION CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT INCRETE MIXES FOR APPROVAL IN AC	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 3-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 4000 PSI 3500 PSI 1500 PSI 1500 PSI CORDANCE WITH A	CEEDING WITH THE WORK. ETAILING, FABRICATION AND S. NCRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED WE THOROUGHLY FAMILIAR WITH DUE TO ACCIDENTAL OVER SPECIAL REQUIREMENTS 5% ±1% AIR CONTENT NO TESTS ACI 301 BEFORE PLACING ANY	 5. MISCELL, A. PROV SHOW B. STEEL PURPC AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV F. PROV F. PROV F. PROV A. PROV ANCHC ANCHC ANCHC ANCHC ANCHC ANCHC ANCHC ANCHC ANCHC DIA DIA DIA DIA DIA DIA DIA DIA
1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONTI 2. CONTINGENCI A. PROVIDE I EXCAVATION 3. CONCRETE RI CLASS 1 2 3 5 SUBMIT CO CONCRETE 4. REINFORCING	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> MS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL CON BARS AND CONCRETE SHALL BE GOV ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F O AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A CON N THE SITE AND THE SUPERVISORY PER ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT ONCRETE MIXES FOR APPROVAL IN ACE. REQUIREMENTS:	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 5-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 4000 PSI 3500 PSI 1500 PSI 1500 PSI CORDANCE WITH A	CEEDING WITH THE WORK. ETAILING, FABRICATION AND S. NCRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED THOROUGHLY FAMILIAR WITH DUE TO ACCIDENTAL OVER SPECIAL REQUIREMENTS 5% ±1% AIR CONTENT NO TESTS ACI 301 BEFORE PLACING ANY	 5. MISCELL, A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV F. PROV F. PROV F. PROV A. PROV ANCHO ANCHO ½" DIA ¾" DIA ¾" DIA ¾" DIA
1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06 B. CRSI RECC C. ACI 306-96 CONTRACT ABOVE ON THE CONTI 2. CONTINGENCI A. PROVIDE I EXCAVATIO 3. CONCRETE RI 2 3 5 SUBMIT CO CONCRETE 4. REINFORCING A. BARS: AS	C. WITH THE ARCHITECTURAL DRAWING REINFORCED (NS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL CON BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A CON N THE SITE AND THE SUPERVISORY PER ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: LOCATION CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR CONCRETE INTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT ONCRETE MIXES FOR APPROVAL IN ACE. REQUIREMENTS: TM A615, A616, A617 - GRADE 60.	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 5-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 4000 PSI 3500 PSI 1500 PSI 1500 PSI CORDANCE WITH A	ETAILING, FABRICATION AND S. NCRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED BE THOROUGHLY FAMILIAR WITH DUE TO ACCIDENTAL OVER SPECIAL REQUIREMENTS 5% ±1% AIR CONTENT NO TESTS ACI 301 BEFORE PLACING ANY	 5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL P. PROV F. PROV RIB FI 6. DRILLED A. PROV ANCHO EVALL APPEI ANCHO ¼" DIA ½" DIA ¾" DIA ¾" DIA ¾" DIA ¾" DIA ¾" DIA
1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONTI 2. CONTINGENCI A. PROVIDE I EXCAVATIO 3. CONCRETE RI 2 3 5 SUBMIT CC CONCRETE 4. REINFORCING A. BARS: AS B. WELDED M 5 FOOTINGS:	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> (NS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COI BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A COR N THE SITE AND THE SUPERVISORY PER ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT DNCRETE MIXES FOR APPROVAL IN AC REQUIREMENTS: TM A615, A616, A617 - GRADE 60. WIRE REINFORCING: ASTM A185.	S PRIOR TO PROC CONCRETE NGRETE WORK, DE VERNED BY: 5-05. REINFORGING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 3500 PSI 1500 PSI 1500 PSI 1500 PSI CORDANCE WITH A	ETAILING, FABRICATION AND S. NGRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED BE THOROUGHLY FAMILIAR WITH DUE TO ACCIDENTAL OVER SPECIAL REQUIREMENTS 5% ±1% AIR CONTENT NO TESTS ACI 301 BEFORE PLACING ANY	 5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV F. PROV RIB FI 6. DRILLED A. PROV ANCHO EVALU APPEN ANCHO ½" DIA
1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONTI 2. CONTINGENCI A. PROVIDE I EXCAVATIO 3. CONCRETE R 2 3 5 SUBMIT CO CONCRETE 4. REINFORCING A. BARS: AS B. WELDED M 5. FOOTINGS: A. DOWELS IN	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> (NS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COL BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A COL N THE SITE AND THE SUPERVISORY PER ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR CONCRETE INTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT ONCRETE MIXES FOR APPROVAL IN ACE. REQUIREMENTS: TM A615, A616, A617 - GRADE 60. WIRE REINFORCING: ASTM A185. N FOOTINGS TO MATCH VERTICAL REIN	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 5-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 4000 PSI 3500 PSI 1500 PSI 1500 PSI 1500 PSI 1500 PSI	CRETE WALLS, COLUMNS OR PIERS.	 5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV RIB FI ORILLED A. PROV ANCHO A
1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONTI 2. CONTINGENCI A. PROVIDE I EXCAVATION 3. CONCRETE RI 2 3 5 SUBMIT CO CONCRETE 4. REINFORCING A. BARS: AS B. WELDED M 5. FOOTINGS: A. DOWELS IN DOWELS IN STRUCTUR	C. WITH THE ARCHITECTURAL DRAWING REINFORCED (NS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COL BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A COL N THE SITE AND THE SUPERVISORY PER ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: LOCATION CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR CONCRETE INTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT ONCRETE MIXES FOR APPROVAL IN ACE. REQUIREMENTS: TM A615, A616, A617 - GRADE 60. WIRE REINFORCING: ASTM A185. N FOOTINGS TO MATCH VERTICAL REIN N FOOTINGS TO MATCH VERTICAL REIN N FOOTINGS TO MATCH VERTICAL REIN N FOOTING TO MASONRY WALLS NOT AL DETAIL 5	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 5-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 4000 PSI 3500 PSI 1500 PSI 1500 PSI 1500 PSI CORDANCE WITH A	CEEDING WITH THE WORK. ETAILING, FABRICATION AND S. NGRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED DE THOROUGHLY FAMILIAR WITH DUE TO ACCIDENTAL OVER SPECIAL REQUIREMENTS 5% ±1% AIR CONTENT NO TESTS ACI 301 BEFORE PLACING ANY CRETE WALLS, COLUMNS OR PIERS. SPECIFICALLY SHOWN ON THE	 5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV RIB FI 6. DRILLED A. PROV ANCHC ANC ANC ANC ANC ANC ANC ANC ANC ANC AN
1. SPECIFICATIO UNLESS SPEC PLACING OF F A. ACI 117-OG B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONT 2. CONTINGENCI A. PROVIDE I EXCAVATIO 3. CONCRETE R 1 2 3 5 SUBMIT CC CONCRETE 4. REINFORCING A. BARS: AS B. WELDED M 5. FOOTINGS: A. DOWELS IN DOWELS IN STRUCTUR B. BEND ALL	C. WITH THE ARCHITECTURAL DRAWING REINFORCED (MS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COL BARS AND CONCRETE SHALL BE GOV 5, ACI 301-05, ACI 315-99, AND ACI 312 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A COL N THE SITE AND THE SUPERVISORY PEI ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR CONCRETE INTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT ONCRETE MIXES FOR APPROVAL IN AC REQUIREMENTS: TM A615, A616, A617 - GRADE 60. WIRE REINFORCING: ASTM A185. N FOOTINGS TO MATCH VERTICAL REIN N FOOTING TO MASONRY WALLS NOT AL DETAILS. BARS 24 DIAMETERS AROUND CORN	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 3-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 4000 PSI 3500 PSI 1500 PSI 1500 PSI 1500 PSI CORDANCE WITH A	CEEDING WITH THE WORK. ETAILING, FABRICATION AND S. NGRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED WE THOROUGHLY FAMILIAR WITH DUE TO ACCIDENTAL OVER SPECIAL REQUIREMENTS 5% ±1% AIR CONTENT NO TESTS ACI 301 BEFORE PLACING ANY CRETE WALLS, COLUMNS OR PIERS. SPECIFICALLY SHOWN ON THE S. BARS AT THE INSIDE FACE OF THE	 5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV RIB FI 6. DRILLED A. PROV ANCHO ANCHO ANCHO ANCHO ANCHO ANCHO STELL C. DRILLED A. PROV B. DIA 3° DI
1. SPECIFICATIO UNLESS SPEC PLACING OF F A. ACI 117-OG B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONT 2. CONTINGENCI A. PROVIDE I EXCAVATIO 3. CONCRETE R 3 5 SUBMIT CC CONCRETE R 4. REINFORCING A. BARS: AS B. WELDED M 5. FOOTINGS: A. DOWELS IN DOWELS IN STRUCTUR B. BEND ALL CORNER S 6. MISCELLANEZ	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> (NS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COL BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND F TOR SHALL AT ALL TIMES HAVE A COL N THE SITE AND THE SUPERVISORY PER ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR CONCRETE INTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT DNCRETE MIXES FOR APPROVAL IN AC E. REQUIREMENTS: TM A615, A616, A617 - GRADE 60. WIRE REINFORCING: ASTM A185. N FOOTINGS TO MATCH VERTICAL REIN N FOOTING TO MASONRY WALLS NOT AL DETAILS. BARS 24 DIAMETERS AROUND CORN SHALL BE CONTINUED ACROSS TO THE DUS:	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 3-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 4000 PSI 3500 PSI 1500 PSI 1500 PSI 1500 PSI CORDANCE WITH A NFORCING IN CONC REQUIRED UNLESS ERS OF FOOTINGS E OUTSIDE AND THE	CRETE WALLS, COLUMNS OR PIERS. 5% 10% AIR CONTENT NO TESTS ACI 301 BEFORE PLACING ANY	 5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CREQUI TEMPI D. STEEL E. PROV F. PROV RIB ED A. PROV ANCHO ANCHO ANCHO ANCHO ANCHO ANCHO ANCHO STRUC IBC 20 ANCHO STRUC IBC 20 ANCHO N" DIA N" DIA
1. SPECIFICATIO UNLESS SPEC PLACING OF F A. ACI 117-OG B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONT 2. CONTINGENCI A. PROVIDE I EXCAVATION 3. CONCRETE R 3 5 SUBMIT CC CONCRETE 4. REINFORCING A. BARS: AS B. WELDED M 5. FOOTINGS: A. DOWELS IN DOWELS IN STRUCTUR B. BEND ALL CORNER S 6. MISCELLANEC A. IF NO OTH	C. WITH THE ARCHITECTURAL DRAWING REINFORCED (NS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COL BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A COL N THE SITE AND THE SUPERVISORY PER ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: LOCATION CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR CONCRETE INTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT DNCRETE MIXES FOR APPROVAL IN AC E. REQUIREMENTS: TM A615, A616, A617 - GRADE 60. WIRE REINFORCING: ASTM A185. N FOOTINGS TO MATCH VERTICAL REIN N FOOTINGS TO MATCH VERTICAL REIN N FOOTING TO MASONRY WALLS NOT AL DETAILS. BARS 24 DIAMETERS AROUND CORN CHALL BE CONTINUED ACROSS TO THE DUS: ER REINFORCING IS SHOWN IN A SLAB	S PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 5-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 4000 PSI 3500 PSI 1500 PSI 1500 PSI 1500 PSI 1500 PSI CORDANCE WITH A NFORCING IN CONC REQUIRED UNLESS ERS OF FOOTINGS OUTSIDE AND THE 3 ON GRADE, PROV	CEEDING WITH THE WORK. ETAILING, FABRICATION AND S. NGRETING, RESPECTIVELY. THE ANT SPECIFICATIONS QUOTED WE THOROUGHLY FAMILIAR WITH DUE TO ACCIDENTAL OVER SPECIAL REQUIREMENTS 5% ±1% AIR CONTENT NO TESTS ACI 301 BEFORE PLACING ANY CRETE WALLS, COLUMNS OR PIERS. SPECIFICALLY SHOWN ON THE S. BARS AT THE INSIDE FACE OF THE EN BENT. VIDE 6x6-W1.4x W1.4 WWR AT	 5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV RIB FI 6. DRILLED A. PROV ANCHC ANCHC 4" DIA %" DIA
1. SPECIFICATIO UNLESS SPEC PLACING OF F A. ACI 117-OG B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONT 2. CONTINGENCI A. PROVIDE F EXCAVATION 3. CONCRETE R 3 5 SUBMIT CC CONCRETE 4. REINFORCING A. BARS: AS B. WELDED M 5. FOOTINGS: A. DOWELS IN STRUCTUR B. BEND ALL CORNER S 6. MISCELLANEC A. IF NO OTH MID-THICK B. LAP WELD	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> (NS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COL BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 312 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND F TOR SHALL AT ALL TIMES HAVE A COL N THE SITE AND THE SUPERVISORY PER ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT INCRETE MIXES FOR APPROVAL IN AC E. REQUIREMENTS: TM A615, A616, A617 - GRADE 60. WIRE REINFORCING: ASTM A185. N FOOTINGS TO MATCH VERTICAL REIN N FOOTING TO MASONRY WALLS NOT AL DETAILS. BARS 24 DIAMETERS AROUND CORN OHALL BE CONTINUED ACROSS TO THE DUS: ER REINFORCING IS SHOWN IN A SLAB NESS OF SLAB. ED WIRE REINFORCING 1 SPACE + 2" A	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 5-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 4000 PSI 3500 PSI 1500 PSI 1500 PSI 1500 PSI CORDANCE WITH A NFORCING IN CONC REQUIRED UNLESS ERS OF FOOTINGS OUTSIDE AND THE 3 ON GRADE, PROV	CRETE WALLS, COLUMNS OR PIERS. SPECIAL REQUIREMENTS 5% ±1% AIR CONTENT NO TESTS ACI 301 BEFORE PLACING ANY CRETE WALLS, COLUMNS OR PIERS. SPECIFICALLY SHOWN ON THE SPECIFICALLY SHOWN ON THE DIE TO ACCIDENTAL OVER	 5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CREQUI TEMPI D. STEEL E. PROV F. PROV F. PROV F. PROV F. PROV 6. DR PROV ANCHO ANCHO 4" DIA %" DIA
1. SPECIFICATIO UNLESS SPEC PLACING OF 1 A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONTI 2. CONTINGENCI A. PROVIDE I EXCAVATIO 3. CONCRETE RI 2 3 5 SUBMIT CC CONCRETE RI 2 3 5 SUBMIT CC CONCRETE 4. REINFORCING A. BARS: AS B. WELDED M 5. FOOTINGS: A. DOWELS IN STRUCTUR B. BEND ALL CORNER S 6. MISCELLANEC A. IF NO OTH MID-THICK B. LAP WELD C. DO NOT B	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> (NS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COI BARS AND CONCRETE SHALL BE GOV , ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND F TOR SHALL AT ALL TIMES HAVE A COI N THE SITE AND THE SUPERVISORY PER ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON CONCRETE UNDER FOUNDATIONS ON SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE INTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT INCRETE MIXES FOR APPROVAL IN AC E. REQUIREMENTS: TM A615, A616, A617 - GRADE 60. URE REINFORCING: ASTM A185. N FOOTINGS TO MATCH VERTICAL REII N FOOTING TO MASONRY WALLS NOT AL DETAILS. BARS 24 DIAMETERS AROUND CORN CHALL BE CONTINUED ACROSS TO THE DUS: ER REINFORCING IS SHOWN IN A SLAB NESS OF SLAB. ED WIRE REINFORCING 1 SPACE + 2" A ACKFILL AGAINST FOUNDATION WALLS	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 5-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL 4000 PSI 3500 PSI 1500 PSI 1500 PSI 1500 PSI 1500 PSI 1500 PSI 1500 PSI CORDANCE WITH A NFORCING IN CONC REQUIRED UNLESS ERS OF FOOTINGS ON GRADE, PROV AT ALL EDGES AND 5 UNTIL BOTH ADJA	CRETE WALLS, COLUMNS OR PIERS. SPECIAL REQUIREMENTS 5% ±1% AIR CONTENT NO TESTS ACI 301 BEFORE PLACING ANY CRETE WALLS, COLUMNS OR PIERS. SPECIFICALLY SHOWN ON THE SPECIFICALLY SHOWN ON THE CRETE WALLS, COLUMNS OR PIERS. SPECIFICALLY SHOWN ON THE SPECIFICALLY SHOWN ON THE SPECIFICALLY SHOWN ON THE SPECIFICALLY SHOWN ON THE SPECIFICALLY SHOWN ON THE SPECI	5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV RIB FI 6. DRILLED A. PROV ANCHO EVALL APPEN ANCHO EVALL APPEN ANCHO EVALL APPEN ANCHO EVALL APPEN ANCHO EVALL APPEN ANCHO EVALL APPEN ANCHO STRUC IBC 20 ANCHO STRUC IBC 20 ANCHO BC 21 ANCHO BC 21 AN
 OPENINGS ET SPECIFICATIO UNLESS SPEC PLACING OF F A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONTR CONTINGENCI A. PROVIDE I EXCAVATIONS CONCRETE RISSING A. PROVIDE I EXCAVATIONS CONCRETE RISSING A. BARS: AS B. WELDED M FOOTINGS: A. DOWELS IN DOWELS IN STRUCTUR B. BEND ALL CORNER SI MISCELLANEC A. IF NO OTH MID-THICK B. LAP WELD C. DO NOT B WHERE FIL DOWELS IN 	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> (NS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COI BARS AND CONCRETE SHALL BE GOV (), ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F O AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A COI N THE SITE AND THE SUPERVISORY PEN- ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR CONCRETE INTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT DNCRETE MIXES FOR APPROVAL IN ACE. REQUIREMENTS: TM A615, A616, A617 - GRADE 60. WIRE REINFORCING: ASTM A185. N FOOTINGS TO MATCH VERTICAL REIN N FOOTING TO MASONRY WALLS NOT AL DETAILS. BARS 24 DIAMETERS AROUND CORN CHALL BE CONTINUED ACROSS TO THE DUS: ER REINFORCING IS SHOWN IN A SLAB NESS OF SLAB. ED WIRE REINFORCING I SPACE + 2" A ACKFILL AGAINST FOUNDATION WALLS I IS ON BOTH SIDES OF A WALL, BRIN 'TON, JOINTS PERMITTED ONLY WINDED I IS ON BOTH SIDES OF A WALL, BRIN 'TON, JOINTS PERMITTED ONLY WINDED I IS ON BOTH SIDES OF A WALL, BRIN 'TON, JOINTS PERMITTED ONLY WINDED I IS ON BOTH SIDES OF A WALL, BRIN 'TON, JOINTS PERMITTED ONLY WINDED I IS ON BOTH SIDES OF A WALL, BRIN 'TON, JOINTS PERMITTED ONLY WINDED I IS ON BOTH SIDES OF A WALL, BRIN 'TON, JOINTS PERMITTED ONLY WINDED I IS ON BOTH SIDES OF A WALL, BRIN 'TON, JOINTS PERMITTED ONLY IN MALLS IN SOULS IN THE ALL AGAINST FOUNDATION WALLS IN SOULS IN STANDATION WALLS IN SOULS IN THE ALL AGAINST FOUNDATION WALLS IN MALL BE CONTINUED ACROSS TO THE DUS: ENTRE REINFORCING IS SHOWN IN A SLAB	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 5-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL 6 FOR EARTH FILL 6 FOR EARTH FILL 1500 PSI 1500 PS	CRETE WALLS, COLUMNS OR PIERS. SPECIAL REQUIREMENTS 5% ±1% AIR CONTENT NO TESTS ACI 301 BEFORE PLACING ANY CRETE WALLS, COLUMNS OR PIERS. SPECIALLY SHOWN ON THE SPECIALLY SHOWN ON THE MO TESTS ACI 301 BEFORE PLACING ANY CRETE WALLS, COLUMNS OR PIERS. SPECIFICALLY SHOWN ON THE SHORE ALLY SHOWN AT SHORE ALLY SHOWN AT SHOWN AT SHORE ALLY SHOWN AT SHOWN AT SHORE ALLY SHOWN AT	5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COR THE M C. GROV REQUI TEMPI D. STEEL E. PROV F. PROV F. PROV F. PROV F. PROV ANCHO EVALL APPEN ANCHO EVALL APPEN ANCHO EVALL APPEN ANCHO EVALL APPEN ANCHO STRUC IBC 20 ANCHO STRUC IBC 20 ANCHO STRUC IBC 20 ANCHO STRUC IBC 20 ANCHO STRUC
 OPENINGS ET SPECIFICATIO UNLESS SPEC PLACING OF F A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONT CONTINGENCI A. PROVIDE I EXCAVATION CONCRETE RISCONCRETE REINFORCING A. BARS: AS B. WELDED M FOOTINGS: A. DOWELS IN DOWELS IN STRUCTUR BEND ALL CORNER S MISCELLANEC A. IF NO OTH MID-THICK LAP WELD C. DO NOT B WHERE FIL D. CONSTRUC ENGINEER. 	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> (NS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COU BARS AND CONCRETE SHALL BE GOV (), ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F O AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A COU N THE SITE AND THE SUPERVISORY PER ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR CONCRETE INTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT ONCRETE MIXES FOR APPROVAL IN ACE. REQUIREMENTS: TM A615, A616, A617 - GRADE 60. WIRE REINFORCING: ASTM A185. N FOOTINGS TO MATCH VERTICAL REIN N FOOTINGS TO MATCH VERTICAL REIN N FOOTINGS TO MASONRY WALLS NOT AL DETAILS. BARS 24 DIAMETERS AROUND CORN CHALL BE CONTINUED ACROSS TO THE DUS: ER REINFORCING IS SHOWN IN A SLAE NESS OF SLAB. ED WIRE REINFORCING I SPACE + 2" A ACKFILL AGAINST FOUNDATION WALLS IS ON BOTH SIDES OF A WALL, BRIN TION JOINTS PERMITTED ONLY WHERE	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 5-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 4000 PSI 3500 PSI 1500 PSI	CRETE WALLS, COLUMNS OR PIERS. SPECIAL REQUIREMENTS 5% ±1% AIR CONTENT NO TESTS ACI 301 BEFORE PLACING ANY CRETE WALLS, COLUMNS OR PIERS. SPECIALS, COLUMNS OR PIERS. SPECIFICALLY SHOWN ON THE BARS AT THE INSIDE FACE OF THE EN BENT. VIDE 6x6-W1.4x W1.4 WWR AT PENDS OF SHEET. ACENT FLOOR SLABS ARE IN PLACE OF FORMLY. PPROVED BY THE STRUCTURAL	5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV RIB ED A. PROV ANCHO ANCHO EVALU APPEN ANCHO 4" DIA 3" DIA
 OPENINGS ET OPENINGS ET SPECIFICATIO UNLESS SPEC PLACING OF F A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONTR 2. CONTINGENCI A. PROVIDE I EXCAVATION 3. CONCRETE RIS 3 CONCRETE RIS CLASS 1 CONCRETE RIS CONCRETE RIS SUBMIT COC CONCRETE CONCRETE RIS SUBMIT COC CONCRETE REINFORCING A. BARS: AS B. WELDED M FOOTINGS: A. DOWELS IN STRUCTUR BEND ALL CORNER S MISCELLANEC A. IF NO OTH MID-THICK LAP WELD C. DO NOT B WHERE FIL D. CONSTRUC ENGINEER. E. PROVIDE C CONVERCE 	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> MS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COL BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A COL N THE SITE AND THE SUPERVISORY PEI ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE INTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT DNCRETE MIXES FOR APPROVAL IN ACE. REQUIREMENTS: TM A615, A616, A617 - GRADE 60. WRE REINFORCING: ASTM A185. N FOOTINGS TO MATCH VERTICAL REII N FOOTING TO MASONRY WALLS NOT AL DETAILS. BARS 24 DIAMETERS AROUND CORN HALL BE CONTINUED ACROSS TO THE DIS: ER REINFORCING IS SHOWN IN A SLAE NESS OF SLAB. ED WIRE REINFORCING 1 SPACE + 2" A ACKFILL AGAINST FOUNDATION WALLS LIS ON BOTH SIDES OF A WALL, BRIN CTION JOINTS PERMITTED ONLY WHERE ONE #4X3'-O" DIAGONAL REINFORCING ONE #4X3'-O" DIAGONAL REINFORCING	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 5-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 4000 PSI 3500 PSI 1500 PSI	CRETE MALLS, COLUMNS OR PIERS. SPECIAL REQUIREMENTS 3% ±1% AIR CONTENT NO TESTS ACI 301 BEFORE PLACING ANY CRETE MALLS, COLUMNS OR PIERS. SPECIALS, COLUMNS OR PIERS. SPECIFICALLY SHOWN ON THE SPECIFICALLY SHOWN ON THE SPECIFICALLY SHOWN ON THE SPECIFICALLY SHOWN S	5. MISCELL/ A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CREQUI TEMPI D. STEEL E. PROV F. PROV RIB ED A. PROV F. PROV RIB ED A. PROV ANCHO ANC
 OPENINGS ET SPECIFICATIO UNLESS SPEC PLACING OF F A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONTR 2. CONTINGENCI A. PROVIDE I EXCAVATION 3. CONCRETE RI 2 3 5 SUBMIT CC CONCRETE 4. REINFORCING A. BARS: AS B. WELDED M 5. FOOTINGS: A. DOWELS IN STRUCTUR B. BEND ALL CORNER S 6. MISCELLANEC A. IF NO OTH MID-THICK B. LAP WELD C. DO NOT B WHERE FIL D. CONSTRUC ENGINEER. E. PROVIDE S 	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> INS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COL BARS AND CONCRETE SHALL BE GOV V, ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING F O AND ACI 305-06 FOR WINTER AND F TOR SHALL AT ALL TIMES HAVE A COL N THE SITE AND THE SUPERVISORY PEI ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR CONCRETE INTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT ONCRETE MIXES FOR APPROVAL IN ACE. REQUIREMENTS: TM A615, A616, A617 - GRADE 60. WIRE REINFORCING: ASTM A185. N FOOTINGS TO MATCH VERTICAL REIN N FOOTING TO MASONRY WALLS NOT AL DETAILS. BARS 24 DIAMETERS AROUND CORN CHALL BE CONTINUED ACROSS TO THE DUS: ER REINFORCING IS SHOWN IN A SLAB NESS OF SLAB. ED WIRE REINFORCING I SPACE + 2" A ACKFILL AGAINST FOUNDATION WALLS IS ON BOTH SIDES OF A WALL, BRING TION JOINTS PERMITTED ONLY WHERE ONE #4X3'-0" DIAGONAL REINFORCING OF SLABS ON GRADE OR SLABS ON SLAB BOLSTERS TO CORRECTLY LOC	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 5-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 4000 PSI 3500 PSI 4000 PSI 3500 PSI 1500 PSI 3000 PSI 1500 PSI	CRETE WALLS, COLUMNS OR PIERS. SPECIAL REQUIREMENTS 3% ±1% AIR CONTENT NO TESTS ACI 301 BEFORE PLACING ANY CRETE WALLS, COLUMNS OR PIERS. SPECIALS SPECIALS CRETE WALLS, COLUMNS OR PIERS. SPECIFICALLY SHOWN ON THE SPECIFICALLY	5. MISCELLA A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV F. PROV F. PROV ANCHC A
 OPENINGS ET SPECIFICATIO UNLESS SPEC PLACING OF F A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONTR 2. CONTINGENCI A. PROVIDE I EXCAVATION 3. CONCRETE RI 2 3 5 SUBMIT CC CONCRETE 4. REINFORCING A. BARS: AS B. WELDED M 5. FOOTINGS: A. DOWELS IN DOWELS IN STRUCTUR B. BEND ALL CORNER S 6. MISCELLANED C. DO NOT B NHERE FIL D. CONSTRUC ENGINEER. E. PROVIDE C CONCRETE 	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> NS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COL BARS AND CONCRETE SHALL BE GOV , ACI 301-05, ACI 315-99, AND ACI 312 DMMENDED PRACTICE FOR PLACING F 0 AND ACI 305-06 FOR WINTER AND H TOR SHALL AT ALL TIMES HAVE A COL N THE SITE AND THE SUPERVISORY PER ES: LEAN CONCRETE UNDER FOUNDATIONS ON C SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR CONCRETE INTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT DNCRETE MIXES FOR APPROVAL IN AC REQUIREMENTS: TM A615, A616, A617 - GRADE 60. URE REINFORCING: ASTM A185. N FOOTINGS TO MATCH VERTICAL REIN N FOOTING TO MASONRY WALLS NOT AL DETAILS. BARS 24 DIAMETERS AROUND CORN CHALL BE CONTINUED ACROSS TO THE DUS: ER REINFORCING IS SHOWN IN A SLAB NESS OF SLAB. ED WIRE REINFORCING 1 SPACE + 2" A ACKFILL AGAINST FOUNDATION WALLS IS ON BOTH SIDES OF A WALL, BRIN TION JOINTS PERMITTED ONLY WHERE ONE #4X3'-O" DIAGONAL REINFORCING 0 SLABS ON GRADE OR SLABS ON SLABS ON GRADE.	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 5-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 4000 PSI 3500 PSI 4000 PSI 3500 PSI 1500 PSI 2007 DANCE WITH A S ON GRADE, PROV AT ALL EDGES AND 5 UNTIL BOTH ADJA NG THE FILL UP UNIF E SHOWN OR AS AF 5 BAR AT MID-DEP METAL DECK. CATE WELDED WIRE	CRETE MALLS, COLUMNS OR PIERS. SPECIAL REQUIREMENTS 5% ±1% AIR CONTENT NO TESTS ACI 301 BEFORE PLACING ANY CRETE MALLS, COLUMNS OR PIERS. SPECIALS, COLUMNS OR PIERS. SPECIFICALLY SHOWN ON THE SPECIFICALLY SPECIFICALLY SPECIFICALY SPECIFICALLY SPECIFICALY SPECIFICALLY SPECIFICALLY SPECIFICAL	5. MISCELLA A. PROV SHOW B. STEEL PURPO AND C COOR THE M C. GROU CRD-C REQUI TEMPI D. STEEL E. PROV F. PROV F. PROV F. PROV F. PROV ANCHC A. PROV ANCHC ANCHC A'' DIA 3'' DIA 3'' DIA 1'' DIA 3'' DIA
 OPENINGS ET SPECIFICATIO UNLESS SPEC PLACING OF I A. ACI 117-06 B. CRSI RECC C. ACI 306-96 CONTRACT ABOVE ON THE CONTI 2. CONTINGENCI A. PROVIDE I EXCAVATION 3. CONCRETE RI 2 3 5 SUBMIT CC CONCRETE 4. REINFORCING A. BARS: AS B. WELDED M 5. FOOTINGS: A. DOWELS IN DOWELS IN STRUCTUR B. BEND ALL CORNER S 6. MISCELLANEC A. IF NO OTH MID-THICK B. LAP WELD C. DO NOT B WHERE FIL D. CONSTRUC ENGINEER. E. PROVIDE C CORNERS F. PROVIDE S CONCRETE 	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> (NS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COI BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING FO 0 AND ACI 305-06 FOR WINTER AND F TOR SHALL AT ALL TIMES HAVE A COI N THE SITE AND THE SUPERVISORY PER ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: <u>LOCATION</u> CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR CONCRETE INTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT INCRETE MIXES FOR APPROVAL IN ACE. REQUIREMENTS: TM A615, A616, A617 - GRADE 60. WIRE REINFORCING: ASTM A185. N FOOTINGS TO MATCH VERTICAL REID N FOOTINGS TO MATCH VERTICAL REID N FOOTING TO MASONRY WALLS NOT AL DETAILS. BARS 24 DIAMETERS AROUND CORN HALL BE CONTINUED ACROSS TO THE DUS: ER REINFORCING IS SHOWN IN A SLAE NESS OF SLAB. ED WIRE REINFORCING IS SHOWN IN A SLAE NESS OF SLAB. ED WIRE REINFORCING I SPACE + 2" A ACKFILL AGAINST FOUNDATION WALLS LIS ON BOTH SIDES OF A WALL, BRINCTION JOINTS PERMITTED ONLY WHERE IS ON BOTH SIDES OF A WALL, BRINCTION JOINTS PERMITTED ONLY WHERE ONE #4X3'-O" DIAGONAL REINFORCING IS ABOLSTERS TO CORRECTLY LOC ESLABS ON GRADE.	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 5-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 4000 PSI 3500 PSI 4000 PSI 3500 PSI 1500 PSI 1500 PSI 1500 PSI 1500 PSI 1500 PSI 1500 PSI 1500 PSI 1500 PSI 2007 DANCE WITH A S ON GRADE, PROV AT ALL EDGES AND 5 UNTIL BOTH ADJA NG THE FILL UP UNIF E SHOWN OR AS AF 5 BAR AT MID-DEP METAL DECK. CATE WELDED WIRE	CRETE WALLS, COLUMNS OR PIERS. SPECIFICALLY SHOWN ON THE NO TESTS ACI 301 BEFORE PLACING ANY CRETE WALLS, COLUMNS OR PIERS. SPECIFICALLY SHOWN ON THE SPECIFICALLY SHOWN ON THE SPECIFICALLY SHOWN ON THE SPECIFICALLY SHOWN ON THE SPECIFICALLY SHOWN ON TH	5. MISCELLA A. PROV SHOW B. STEEL PURD C COR COR COR COR COR CREQUI TEMPI D. STEEL E. PROV F. PROV F. PROV F. PROV F. PROV ANCHC A. PROV ANCHC
1. SPECIFICATIO UNLESS SPEC PLACING OF F A. ACI 117-06 B. CRSI RECC C. ACI 306-90 CONTRACT ABOVE ON THE CONT 2. CONTINGENCI A. PROVIDE I EXCAVATIO 3. CONCRETE R 3 5 SUBMIT CC CONCRETE 4. REINFORCING A. BARS: AS B. WELDED M 5. FOOTINGS: A. DOWELS IN DOWELS IN STRUCTUR B. BEND ALL CORNER S 6. MISCELLANEC A. IF NO OTH MID-THICK B. LAP WELD C. DO NOT B WHERE FIL D. CONSTRUC ENGINEER. E. PROVIDE S CONCRETE	C. WITH THE ARCHITECTURAL DRAWING <u>REINFORCED</u> (NS AND STANDARDS: IFICALLY SHOWN OTHERWISE, ALL COL BARS AND CONCRETE SHALL BE GOV 0, ACI 301-05, ACI 315-99, AND ACI 318 DMMENDED PRACTICE FOR PLACING FO 0 AND ACI 305-06 FOR WINTER AND F TOR SHALL AT ALL TIMES HAVE A COL 1 THE SITE AND THE SUPERVISORY PEI ENTS THEREOF. ES: LEAN CONCRETE UNDER FOUNDATIONS ON OR SOFT SPOTS. EQUIREMENTS AND LOCATION IN JOB: LOCATION CAISSONS AND ALL INTERIOR CONCRETE NOT OTHERWISE NOTED. EXTERIOR SLABS, GRADE BEAMS, & SLABS ON METAL DECK EARTH FILL & MUDMAT INCRETE MIXES FOR APPROVAL IN ACE. 7 REQUIREMENTS: TM A615, A616, A617 - GRADE 60. URE REINFORCING: ASTM A185. N FOOTINGS TO MATCH VERTICAL REIN N FOOTINGS TO MATCH VERTICAL REIN N FOOTING TO MASONRY WALLS NOT AL DETAILS. BARS 24 DIAMETERS AROUND CORN SHALL BE CONTINUED ACROSS TO THE 205: ER REINFORCING IS SHOWN IN A SLAE NESS OF SLAB. ED WIRE REINFORCING IS SHOWN IN A SLAE NESS OF SLABS ON GRADE OR SLABS ON SLAB SON	SS PRIOR TO PROC CONCRETE NCRETE WORK, DE VERNED BY: 5-05. REINFORCING BARS HOT WEATHER CON PY OF THE RELEVA RSONNEL SHALL B S FOR EARTH FILL <u>F'C</u> 3000 PSI 3500 PSI 4000 PSI 3500 PSI 1500 PSI 2007 DANCE WITH A S FORCING IN CONC REQUIRED UNLESS ERS OF FOOTINGS FOUTSIDE AND THE 3 ON GRADE, PROV AT ALL EDGES AND 5 UNTIL BOTH ADJA NG THE FILL UP UNIF E SHOWN OR AS AF 5 BAR AT MID-DEP METAL DECK. CATE WELDED WIRE	CRETE WALLS, COLUMNS OR PIERS. SPECIFICALLY SHOWN ON THE NO TESTS ACI 301 BEFORE PLACING ANY CRETE WALLS, COLUMNS OR PIERS. SPECIFICALLY SHOWN ON THE BARS AT THE INSIDE FACE OF THE SPECIFICALLY SHOWN ON THE BARS AT THE INSIDE FACE OF THE NO TESTS ACI 301 SEFORE PLACING ANY CRETE WALLS, COLUMNS OR PIERS. SPECIFICALLY SHOWN ON THE BARS AT THE INSIDE FACE OF THE NO BARS AT THE INSIDE FACE OF THE STRUCTURAL NO FOR SLABS AT ALL RE-ENTRANT E REINFORCING AT MID-DEPTH OF	5. MISCELLA A. PROV SHOW B. STEEL PURPO AND C CORPT AND C CORPT AND C CORPT AND C CORPT C. GROUT C. GR

ATIONS AND STANDARDS:

SPECIFICALLY SHOWN OTHERWISE, DESIGN, FABRICATION AND ERECTION SHALL BE LED BY THE LATEST REVISIONS OF: SPECIFICATION FOR THE DESIGN, FABRICATION, AND ERECTION OF STRUCTURAL

FOR BUILDINGS. ASD-13th EDITION CODE OF STANDARD PRACTICE - 2005.

STANDARD WELDING SYMBOLS.

CTURAL WELDING CODE AWS D1.1-2006 OF THE AMERICAN WELDING SOCIETY. NING SHALL BE PERFORMED ONLY BY OPERATORS QUALIFIED, BY THE AWS DARD QUALIFICATION PROCEDURE, TO PERFORM THE PARTICULAR TYPE OF WORK

IRED. IFICATIONS FOR STRUCTURAL JOINTS USING ASTM A325 OR A490 BOLTS - 2004.

DS: VISUAL TESTING SHALL BE PERFORMED BY AN

PENDENT TESTING LABORATORY ON ALL CRITICAL WELDS AND ON 25% OF RITICAL WELDS. INADEQUATE WELDS SHALL BE STRENGTHENED OR CUT OUT AND ACED AS DIRECTED. CRITICAL WELDS SHALL BE DEFINED AS ALL FULL

TRATION WELDS, ALL WELDS IN MOMENT CONNECTIONS AND AS NOTED AS CRITICAL DS ON THE STRUCTURAL DETAILS. CTURAL STEEL: PROVIDE MILL REPORTS FOR PROPERLY IDENTIFIED MATERIALS ON EST.

AND A490 BOLTS: PROVIDE BOLT INSPECTION AS DETAILED IN PARAGRAPH 9 OF FICATIONS FOR STRUCTURAL JOINTS USING A325 OR A490 BOLTS.

HAPES: ASTM A992 Fy = 50 KSI

NELS: ASTM A36 ES, PLATES AND BARS: ASTM A36.

ING ELECTRODES: AWS A5.1 OR A5.5 SERIES E70. 5: ASTM A325.

OR BOLTS: ASTM F1554 GR.36

AND PROTECTION: RIME COAT, TOUCH UP AFTER ERECTION.

IMBERS TO BE ENCASED IN CONCRETE OR SPRAY-ON FIRE PROOFING: NO PAINT. MBERS EXPOSED TO WEATHER IN FINISHED STRUCTURE: GALVANIZED AFTER

BRICATION. TION REQUIREMENTS:

5N CONNECTIONS FOR VERTICAL REACTIONS SHOWN ON DRAWINGS OR FOR FULL CAPACITY OF BER WHERE NO REACTION IS SHOWN.

5N MOMENT BEAM CONNECTIONS FOR VALUES SHOWN OR FOR FULL MOMENT CAPACITY OF ER. IECTIONS SHOWN AND DETAILED ON THE DRAWINGS MAY BE REDESIGNED BY THE STRUCTURAL

. CONTRACTOR FOR EQUAL FORCES PROVIDED THE SAME ARRANGEMENT OF MEMBERS IS USED THE OVERALL SIZE OF THE CONNECTION DOES NOT EXCEED THAT OF THE CONNECTION LED.

IN APPROVAL FROM STRUCTURAL ENGINEER FOR TYPES OF CONNECTIONS BEFORE CATION.

BOLTED CONNECTIONS TO BE SHEAR/BEARING TYPE WITH BOLTS IN THE SNUG TIGHT CONDITION SS NOTED OTHERWISE.

ANEOUS REQUIREMENTS:

/IDE HOLES FOR OTHERS. IF SECTION IS WEAKENED BY MORE THAN 15% BY AN OPENING NOT IN ON THE DRAWINGS, OBTAIN PRIOR APPROVAL. . SUPPORTING OR CONNECTING TO MECHANICAL OR OTHER EQUIPMENT IS SHOWN FOR BIDDING

OSES ONLY. CONTRACTOR SHALL RECONCILE EXACT SIZE AND LOCATION WITH MECHANICAL OTHER REQUIREMENTS BEFORE PROCEEDING WITH THE WORK. CONTRACTOR SHALL RDINATE EXACT SIZE AND LOCATION FOR ALL STEEL ANGLE FRAMES WITH OPENINGS SHOWN ON 1ECHANICAL AND ARCHITECTURAL DRAWINGS. JT UNDER BEARING PLATES TO BE NON-SHRINKING TYPE MEETING ALL THE REQUIREMENTS OF

C621, CORPS OF ENGINEERS SPECIFICATION FOR NON-SHRINK GROUT OR MEETING ALL REMENTS OF ASTM C1107 FOR FLUID CONSISTENCY, 30 MINUTE WORKING TIME AND ERATURE RANGE FROM 45°F TO 90°F.

. BELOW GRADE TO BE PROTECTED BY A MINIMUM OF 3" OF CONCRETE OR 4" OF MASONRY. /IDE HEAVY WASHER AT ALL ANCHOR BOLTS. IDE ANGLE SUPPORTS FOR ALL METAL DECK RIBS AT COLUMNS WHEN COLUMN SIZE PREVENTS

ROM CONTINUING TO BEAM WHICH IS SUPPORTING DECK AT COLUMN LINE. ANCHORS: IDE DRILLED ANCHORS AS INDICATED ON THE STRUCTURAL DRAWINGS. DRILLED EXPANSION

ORS SHALL BE WEDGE TYPE WITH ONE PIECE WRAP AROUND EXPANSION CLIP. THE ENTIRE OR SHALL BE CARBON STEEL MEETING THE FOLLOWING REQUIREMENTS, AND SHALL BE UATED TO COMPLY WITH IBC 2006 INCLUDING, BUT NOT LIMITED TO, SECTION 1912 AND ACI 318 NDIX D SECTION D.3.3.

<u>OR SIZE</u>	MINIMUM EMBE	EDMENT PU	<u>ILLOUT (LBS,</u>) <u>SHEAR (L</u>	<u>_BS)</u>	
METER	2"		550	590		
METER	2 ½"		1050	1300		
METER	3½"		1700	2200		
METER	4"		2400	3300		
METER	4 ¾''		3250	4650		
METER	6"		6400	7450		
S INDICATED	ABOVE ARE	SERVICE LOADS	IN POUNDS	FOR STAINLESS	STEEL ANCHORS	IN 3000

ONE AGGREGATE CONCRETE. ANCHORS:

/IDE DRILLED ANCHORS EMBEDDED IN ADHESIVE AS INDICATED ON THE TIPAL DRAMINGS THE ENTIRE ANCHOR SYSTEM SHALL BE EVALUATED TO COMPLY WITH

	AMINGS. THE ENTIRE AND	HOR SISIEM SHALL	DE EVALUATED TO COMPLI	
006 INCLU	DING, BUT NOT LIMITED TO	, SECTION 1912 AND A	CI 318 APPENDIX D SECTIO	N D.3.3.
OR SIZE	MINIMUM EMBEDMENT	<u>PULLOUT (LBS)</u>	<u>SHEAR (LBS)</u>	
AMETER	3½"	1800	1050	
AMETER	44"	2700	1900	
AMETER	5"	4300	3000	
AMETER	7"	4650	4350	
AMETER	7"	7800	5900	
METER	84"	14500	9600	
'S INDICATED ABOVE ARE SERVICE LOADS FOR ANCHORS IN 3000 PSI STONE AGGREGATE				
RETE.				

STEEL DECK

ECIFICATIONS AND STANDARDS: INLESS SPECIFICALLY SHOWN OTHERWISE, DESIGN FABRICATION AND ERECTION OF STEEL DECK SHALL BE GOVERNED BY THE LATEST EDITION OF THE AMERICAN IRON AND STEEL NSTITUTE, SPECIFICATION FOR THE DESIGN OF COLD-FORMED STEEL STRUCTURAL

MEMBERS. ALL PROPERTIES OF THE STRUCTURAL STEEL DECK SHALL BE COMPUTED IN ACCORDANCE NITH THE REFERENCE STANDARD. THE PROPERTIES SHALL BE PUBLISHED IN THE

MANUFACTURER'S CATALOG. C. AWS STANDARD WELDING SYMBOLS.

D. ANS D1.3 SPECIFICATIONS FOR WELDING SHEET STEEL IN STRUCTURES. E. WELDING SHALL BE PERFORMED ONLY BY OPERATORS QUALIFIED, BY THE AWS STANDARD QUALIFICATION PROCEDURE, TO PERFORM THE PARTICULAR TYPE OF WORK REQUIRED.

2. MATERIALS: A. GALVANIZED STEEL DECK: ASTM A653 STRUCTURAL QUALITY GRADE 33 WITH COATING

DESIGNATION G60. B. WELDING ELECTRODES: AWS A5.1, A5.5 OR A5.18 SERIES E60.

3. ERECTION AND CONNECTIONS:

A. STEEL DECK UNITS AND ACCESSORIES SHALL BE AS SHOWN ON THE MANUFACTURER'S ERECTION DRAWINGS.

B. MINIMUM BEARING OF THE DECK SHALL BE 2 INCHES UNLESS OTHERWISE SHOWN.

C. ANCHOR STEEL DECK TO STEEL SUPPORTING MEMBERS WITH 56" PUDDLE WELDS AT A MAXIMUM AVERAGE SPACING OF 12 INCHES UNLESS SHOWN OTHERWISE. D. SIDELAPS SHALL BE FASTENED BY MEANS OF A #10 SCREW AT MIDSPAN BETWEEN SUPPORTS

UNLESS SHOWN OTHERWISE. 4. OPENINGS IN STEEL DECK:

A. OPENINGS CUT IN THE STEEL DECK SHALL BE REINFORCED OR SHALL BE SUPPORTED ON STEEL ANGLE FRAMES. COORDINATE SIZES AND LOCATIONS WITH THE MECHANICAL AND ARCHITECTURAL DRAWINGS.

B. OPENINGS IN STEEL DECK EQUAL TO OR LESS THAN 12"X12" SHALL BE REINFORCED WITH A 24"X24" -16 GAGE PLATE SCREWED OR WELDED TO THE DECK RIBS ON ALL SIDES OF THE OPENING. C. OPENINGS IN ROOF DECK GREATER THAN 12"X12" SHALL BE SUPPORTED ON STEEL ANGLE FRAMES.









OSU-090344



ASSOCIATE:				
	ross barney architects			
ARCHITECTURE	D arc			
424 East Fourth Street Cincinnati Obio 45202	10 West Hubbard Street			
TEL (513) 241-4474	Chicago, Illinois 60654 Tel. (312) 832 0600			
	Fax. (312) 832 0601			
UNUT NGINEERIA CHI				
5520 Research Park Drive	RAUSCH 430 South Front Street Columbus, Ohio 43215			
Baltimore, Maryland 21228 Tel. (410) 576 0505	ARCHITECTURE + Tel. (614) 224 9050 Fax. (614) 233 6929			
Fax. (410) 385 0327		10	1011	
SHELLEY	Iones-	18	4-6-11	Bulletin 01
BAUMANN	Stuckey	9	12-22-10	Bid Docum
НАШК	Ltd., Inc. 2323 W. Fifth Avenue	7	12-14-10	Bid Docum
1166 Dublin Road, Suite 200 Columbus, Obio 43215	Columbus, Ohio 43204	6	11-17-10	Bid Docum
Tel. (614) 481 9800 Fax. (614) 481 9353	Tei. (614) 486 0410 Fax. (614) 486 1194	5	10-15-10	Bid Docum
1 42. (014) 401 3035		4	09-17-10	Bid Docum
		3	07-26-10	ISSUED F
MSI	5875 Landerbrook Drive	2	07-22-10	CD - BID F
462 South Ludlow Alley Columbus, Ohio 43215	WHITING-TURNER Suite 100 Cleveland, Ohio 44124	1	05-07-10	DD - ADD
Tel. (614) 621.2796 Fax. (614) 621.3604	Tel. (440) 449 9200 Fax. (440) 449 9203	NO.	DATE	
	NOT FOR CONSTRUCTION			
NAADTINI				
PIAKHIN				
5955 Wilcox Place			,	300111
Dublin, Ohio 43016 Tel. (614) 761.5600				
Fax. (614) 761.5601	() DESIGN DEVELOPMENT			
THIS DOCUMENT			F	
WAS ORIGINALLY				
ISSUED				
BY STEPHEN J				
METZ ON 7-22-10.				
THIS DOCUMENT		42	4 EAST FOU	IRTH STREE
IS NOT				
CONSIDERED A				SEC
SEALED				
DOCUMENT.		0.011		
		0.5.0.	PROJ. NO.	



ASSOCIATE:				
	ross barney architects			
ARCHITECTURE	F D arc			
424 East Fourth Street	10 West Hubbard Street			
TEL (513) 241-4474	Chicago, Illinois 60654 Tel. (312) 832 0600			
FAX (513) 241-0081	Fax. (312) 832 0601			
CONSULTANTS:				
NUMMINING IN EER IN GUILE				
	LUPTON			
	RAUSCH 430 South Front Street			
Baltimore, Maryland 21228	ARCHITECTURE + Tel. (614) 224 9050 Env. (614) 222 9020			
Fax. (410) 378 0303	INTERIOR DESIGN			
SHELLEY		18	4-6-11	Bulletin 01
METZ	Jones-	9	12-22-10	Bid Packa
HAWK	Stuckey	8	12-14-10	Bid Docum
STRUCTURAL ENGINEERING	Ltd., IIIC. 2323 W. Fifth Avenue Suite 160	7	11-30-10	Bid Docum
Columbus, Ohio 43215	Columbus, Ohio 43204 Tel. (614) 486 0410	6	11-17-10	Bid Docum
Fax. (614) 481 9800 Fax. (614) 481 9353	Fax. (614) 486 1194	5	10-15-10	Bid Docum
		4	09-17-10	Bid Docum
		3	07-26-10	ISSUED F
MSI	5875 Landerbrook Drive	2	07-22-10	CD - BID F
462 South Ludlow Alley Columbus, Ohio 43215	WHITING-TURNER Cleveland, Ohio 44124		05-07-10	DD - ADDI
Tel. (614) 621.2796 Fax. (614) 621.3604	Tel. (440) 449 9200 Fax. (440) 449 9203	NO.	DATE	
	NOT FOR CONSTRUCTION			
MADTINI				
5955 Wilcox Place			,	500111
Dublin, Ohio 43016 Tel. (614) 761.5600				
Fax. (614) 761.5601	() DESIGN DEVELOPMENT			
THIS DOCUMENT	CONSTRUCTION DOCUMENTS		F	
WAS OBIGINALLY			•	
ISSUED				
BV STEPHEN I				
METZ ON 7-22-10				
THIS DOCUMENT		42	24 EAST FOL	IRTH STREE
IS NOT				
				SEC
			i	
		0.S.U.	PROJ. NO.	FILENAME
				1.0260/4066